



345 Carlingview Drive
Toronto, Ontario M9W 6N9
Tel.: 416.734.3300
Fax: 416.231.1626
Toll Free: 1.877.682.8772

www.tssa.org

June 29, 2021

MISTER CRN CONSULTING INC.
PO BOX 488
MONTAGUE PE C0A 1R0

Workorder Type: Registration - Fitting(Conventional)
Workorder No: SR3019836
Your Reference No.: LOG 2769
Registered to: AALBERTS INTEGRATED PIPING SYSTEM APAC INC.

Dear MILLER WEST,

Technical Standards and Safety Authority (TSSA) is pleased to inform you that your submission has been reviewed and registered as follows:

CRN : 0B1967.75R2
Main Design No.: 0B1967.75R1 RENEWAL AND COMPANY NAME CHANGE
Expiry Date: Dec 18, 2030

Please be advised that a valid quality control system must be maintained for the fitting registration to remain valid until the expiry date.

R2: CRN RENEWAL AND COMPANY NAME CHANGE

The stamped copy of the approved registration and the invoice are mailed separately (There will be no hard copies for electronic submissions). Should you have any questions or require further assistance, please contact a Customer Service Advisor at 1.877.682.TSSA (8772) or e-mail customerservices@tssa.org. We will be happy to assist you. When contacting TSSA regarding this file, please refer to the Service Request number provided above.

Yours truly,

Norman Ngai

Norman Ngai P. Eng. Mechanical Engineer
Engineer, BPV
Tel. : +1 416-734-3557
Email : NNgai@tssa.org

CRN Registration

Oct. 30, 2020

Shurjoint Grooved Components are to be registered (Category B - Flanges)

| Model Number | Size Range (inch) | Rated Pressure (psi) | Service Temperature | Drawings |
|---|------------------------------|----------------------|--|-----------------------------------|
| 7170 Flange Adapter | 2 ~ 8 | 300 | -20°F ~ +180°F (-29°C ~ +82°C) | 170 |
| 7180 Universal Flange Adapter | 2 ~ 8 | 300 | -20°F ~ +180°F (-29°C ~ +82°C) | 180 |
| 7181 Universal Reducing Flange Adapter | 3 x 2, 4 x 2½, 4 x 3, 6 x 4 | 125 | -20°F ~ +180°F (-29°C ~ +82°C) | 1AG |
| 7041 Flange Adapter | 2 ~ 6 | 300 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | HA104a |
| | 10 ~ 12 | 175 | | |
| 7043 Flange Adapter - ANSI Class 300 | 2, 2½, 3, 4, 5, 6, 8, 10, 12 | 200 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-7043 H143 G14a 7041HB |
| SS-41 Flange Adapter | 2, 2½, 3, 4, 6, 8 | 175 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-SS41 H1SG G14a 7041HB |
| SS-80 Stainless Steel Universal Flange Adapter | 2, 2½, 3, 4, 5, 6, 8 | 250 | -20°F ~ +180°F (-29°C ~ +82°C) | 1S9 |
| C341 Flange for Copper Tubing | 2, 2½, 3, 4, 5, 6 | 200 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-C341 1C5 GC5 7041HB |