## UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUNAVUT	NOVA SCOTIA YUKON	PRINCE EDWARD ISLAND NORTHWEST TERRITORIES	NEWFOUNDLAND AND LABRADOR
MANUFACTURERS NAME:	Aalberts integrated piping s	ystems APAC	
MANUFACTURERS ADDRESS:	No. 295, Sec. 3, Wandan Ro	oad, Wandan Township, Pingtung, Taiwan	R.O.C.
PLANT LOCATIONS:	As above		
CATEGORY OF FITTI	NGS TO BE REGISTERED. (	CIRCLE ONE CATEGORY ONLY	TITLE OF THE STANDARD OF CONSTRUCTION
A Pipe fittings, including coupling B Flanges: all flanges © Valves: all line valves D Expansion joints, flexible conn E Strainers, filters, separators, a F Measuring devices, including pressure transmitters G Certified capacity-rated pressure boilers, pressure vessels, pipi H Pressure retaining component	nections, and hose assemblies and steam traps pressure gauges, level gauges ure relief devices acceptable a ing and fusible plugs	: all types s, sight glasses, levels, or as primary over pressure protection on	ASME B31.3
		Meeting CNSC or ASME requirements)	
		AS IT WILL APPEAR ON THE PRODUCT	TYPE OF CONSTRUCTION
西	and/or SHU	JRJOINT	FORGED   WELDED   WROUGHT   CAST   OTHER   DESCRIBE OTHER
		ATION OF THE ACTUAL ITEMS TO BE R	EGISTERED:
- LRQA certificate of approval No - Renew 0C1968.7C.	a: ISO 9001 - 0068440		
- Renew 0C1968.7C See document *CRN Registrati	ion" dated Oct. 30, 2020, draw	rings & proof test records.	
my knowledge represents the temperature ratings, and ident manufacture of these fittings is or in part and has been verified declaration conscientiously be	the end product do solem product for which registrat tification markings are in a regulated by a Quality Cod by LRQA certificate No. ISC elieving it to be true, and kr	nly declare that the information contain ion is sought. The dimensions, materia coordance with the herein named standartol Program which extends to each po 1000 - 0068440 as being suitable for the same force and decimals and the same force and decimals are some some suitable for the same force and decimals are some some same force and decimals are some some same some same some same some same same some same same same same same same same sa	lards. I further declare that the plant where fabrication occurs in whole that purpose and I make this solemn
Signature of Declarer: CH	IN, YING CHL	IAN	
Declared before me at Kach	nslung	luce Tue	S S PACE FO
- A - 11-	202		New of Nouveau
This 2077 day of No	AD 2021	0 13	rinswick
Commissioner of Daths	Juma Chi-	1-974-1	T SAN TO A A WARM OF
or Notary Public: (sign)		- Doug	- "IOTIOT DUDI IO CAFETY
·mi		The state of the s	F JUSTICE PUBLIC SAFETY
11111	This sp	pace for Regulatory Authority use BOILER	& PRESSURE VESSELACT
0C1068 7 Pov	registration must be revali	BOILER	& PRESSURE VESSELACT
CRN: 0C1968.7 Rev	registration must be revali	pace for Regulatory Authority use BOILER	& PRESSURE VESSEL ACT
CRN: 0C1968.7 Rev. 16031  FID#: Rev. is CRN renewal and com Aalberts Integrated Piping Sys Succession SJ-300N, SJ-200, SJ-300N, SJ-300N	pany name change from Shetems APAC Inc. Model SJ-300F, 680 butterfly valves,	cace for Regulatory Authority use BOILER dated after ten (10) years from the date can be called a carbon ten (10) years from the date can be called a carbon ten (10) years from the date carbon ten (10) years from ten (10)	REGISTRATION ONLY  OC1968, 7 Lev 2  Con Curs
CRN: 0C1968.7 Rev.  16031  FID#: Rev. is CRN renewal and com Aalberts Integrated Piping Sys \$1,400, SJ-300N, SJ-200, SJ Notes.  1. All fittings shall be registered. Each category shall be suppforms and one copy of supporting. The declaration shall be managed.	pany name change from Statems APAC Inc. Model SJ-300F, 680 butterfly valves, d in the name of the Manufact ported with two Statutory Decing documentation.	cace for Regulatory Authority use BOILER dated after ten (10) years from the date can be caused after ten (10) years from the date can be can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be can be can be can be can be can be can	& PRESSURE VESSELACT
CRN: 0C1968.7 Rev.  16031 Rev. is CRN renewal and com Alberts Integrated Piping Sys S.1-400, SJ-300N, SJ-200, SJ- Notes.  1. All fittings shall be registered. 2. Each category shall be supported by the second of supports. 3. The declaration shall be made responsibility for the quality of the second of the sec	pany name change from Statems APAC Inc. Model SJ-300F, 680 butterfly valves, d in the name of the Manufact ourted with two Statutory Declaring documentation. de by the person having full at the end product.	cace for Regulatory Authority use BOILER dated after ten (10) years from the date can be caused after ten (10) years from the date can be can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be can be can be can be can be can be can	REGISTRATION ONLY  OC 1968, 7 Les 2  Con Cours  DEF BOILER INSPECTOR  TE 12/18/20
CRN: 0C1968.7 Rev.  16031  FID#: Rev. is CRN renewal and com Aalberts Integrated Piping Sys \$1,400, SJ-300N, SJ-200, SJ Notes. 1.400, SJ-300N, SJ-200, SJ Notes. 2. Each category shall be suppforms and one copy of supporti	pany name change from Statems APAC Inc. Model SJ-300F, 680 butterfly valves, d in the name of the Manufact borted with two Statutory Declared documentation. de by the person having full at the end product.	cace for Regulatory Authority use BOILER dated after ten (10) years from the date can be caused after ten (10) years from the date can be can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be caused after ten (10) years from the date can be can be can be can be can be can be can	REGISTRATION ONLY  OC1968, 7 Lev 2  Con Curs

## **CRN Registration**

Shurjoint Grooved Components are to be registered (Category C -Valves)

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-C300 Butterfly Valve for Copper Tubing	2, 21/2, 3, 4, 5, 6	150	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJC300 1CKa 1CKb 1CKc
SJ-600 Ball Valve	1½, 2, 2½, 3, 4	300	-20°F ~ +230°F (-7 °C ~ +110°C)	AS-SJ600SS-a AS-SJ600SS-b 1SXa 1SXb 1SXc 1SXd 1SXd
SJ-400 Butterfly Valve	3, 4	250	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ400 1CNa 1CNb 1CNc
SJ-300N Butterfly Valve	2, 21/2, 3, 4	300	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJ300N 1J3a 1J3b 1J3c
RCV Riser Check Valve	2½, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-RCV 1RVa 1RVb
	8	125		1RVc 1RVd 1RVe 1RVf
SJ-200 Low Profile Butterfly Valve	2, 2½, 3, 4, 6	125	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ200 1JNa 1JNb 1JNc 1JNd

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-300F Resilient Seated Butterfly Valve	2½, 3, 4, 5, 6	200	EPDM: -20°F + +180°F (-29°C ~ +82°C)	AS-SJ300F AS-SJ300F-a 1JLa 1JLb 1JLc 1JLd 1JLe 1JLf 1JLf
SJ-500L	1½, 2, 2½, 3	250	EPDM:	
Ball Valve	4, 6	200	$-20^{\circ}\text{F} \sim +180^{\circ}\text{F}$ $(-29^{\circ}\text{C} \sim +82^{\circ}\text{C})$	SJ500-C-3
SJ-900 Swing Check Valve	2½, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F	AS-SJ900 1J9a 1RVb 1RVc
	8	150	(-29°C ~ +82°C)	1RVd 1RVe 1RVf
SJ-930 Horizontal Swing Check Valve	2, 21/2, 3, 4	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ930 1AJa 1AJb 1AJc AS-7771 H108a AS-XH70EP H1X8 G15a 7705TB 160a S819001
SJ-915 Dual Disc Check Valve	2½, 3, 4, 6, 8	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ915 AS-SJ915_b
	10, 12	150		1JKa 1JKb
	14, 16, 18, 20, 24	100		1JKc 1JKd 1JKe