## UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

EW BRUNSWICK UNAVUT	NOVA SCOTIA YUKON	PRINCE EDWARD ISLAND NORTHWEST TERRITORIES	NEWFOUNDLAND AND LABRADOR			
ANUFACTURERS NAME:	Aalberts integrated pip	ing systems APAC	1			
MANUFACTURERS ADDRESS:	No. 295, Sec. 3, Wandan Road, Wandan Township, Pingtung, Taiwan R.O.C.					
PLANT LOCATIONS:	As above					
CATEGORY OF FITTH	IGS TO BE REGISTER	ED. CIRCLE ONE CATEGORY ONLY	TITLE OF THE STANDARD OF CONSTRUCTION			
B Flanges: all flanges  O Valves: all fine valves  D Expansion joints, flexible conn  E Strainers, filters, separators, all  F Measuring devices, including p  pressure transmitters	ections, and hose assert nd steam traps tressure gauges, level ga tre relief devices accepts ng and fusible plugs	auges, sight glasses, levels, or able as primary over pressure protection on	ASME 831.3			
옷이 되는 집에 가는 것이 되었다. 이 사이와 그 아니스 생각이 되었다. 이 사이를 살아 먹는 것이 되었다.		D. (Meeting CNSC or ASME requirements)				
	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	OGO AS IT WILL APPEAR ON THE PRODUC	T IYPE OF CONSTRUCTION			
		IURJOINT	FORGED CI WELDED CI WROUGHT CI CAST & OTHER CI DESCRIBE OTHER			
LIST OF SUPPORTING DOCUM	ENTATION AND IDENT	IFICATION OF THE ACTUAL ITEMS TO BE	REGISTERED:			
by knowledge represents the permental representation of the permeters of t	the end product do so product for which regis fication markings are	ed bysations integrated plains systems AFAC in- and I lemnly declare that the information contai stration is sought. The dimensions, mater in accordance with the herein named star	ned in this form is true and to the best of ials of construction, pressure starts. I further declare that the			
in part and has been verified	by LRQA certificate No	y Control Program which extends to each 18O 9001 – 0068440 as being suitable for d knowing that it is of the same force and	that purpose and I make this solemn			
ignature of Declarer: CH:	FU, YING C	HUAN				
eclared before me at Kaohs	lung	USETHI	S SPACE FO			
f t	ember AD	2020	SIGIAL BEAL			
tommissioner of Peths r Notary Public (sign)		i-Long				
× ==	i i Th	is space for Regulatory Authority use	£2,			
		validated after ten (10) years from the dat	e of acquetaficendland			
CRN: 0C1968.7 Rev2	.'		Labrador			
16031	•	_	Service NL			
FIDM: Rev. is UKIN renewal and comp Aelberts Integrated Piping Syst \$15400, SJ-300N, SJ-200, SJ-3	ems APAC Inc. Model	n Shurjoint to SJ-C300, [	Registered UC 1960 . 70 (EV.2) Date			
<ol> <li>All fittings shall be registered</li> <li>Each category shall be supported forms and one copy of supporting</li> </ol>	in the name of the Manu rted with two Statutory D	facturer.	Registered by			
3. The declaration shall be made	s by the person having h	ull authority and	UNDER THE AUTHORITY OF THE			
responsibility for the quality of the 4. Quality control programs shall		fation 1	PUBLIC SAFETY ACT AND THE BOILER, PRESSURIL VESSEL AND			
at a maximum interval of five (5) SJ-500L, 835 ball valves; RCV,		5 check valves	COMPRESSED 100/SFREIGHLAGION \$5/2003			
CO COUL, OUD DAIL VAIVES, NOV,	00000, 00-900, 00-91	o ollock valvas.				

## **CRN Registration**

Shurjoint Grooved Components are to be registered (Category C -Valves)

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-C300 Butterfly Valve for Copper Tubing	2, 21/2, 3, 4, 5, 6	150	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJC300 1CKa 1CKb 1CKc
SJ-600 Ball Valve	1½, 2, 2½, 3, 4	300	-20°F ~ +230°F (-7 °C ~ +110°C)	AS-SJ600SS-a AS-SJ600SS-b 1SXa 1SXb 1SXc 1SXd 1SXd
SJ-400 Butterfly Valve	3, 4	250	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ400 1CNa 1CNb 1CNc
SJ-300N Butterfly Valve	2, 21/2, 3, 4	300	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJ300N 1J3a 1J3b 1J3c
RCV Riser Check Valve	2½, 3, 4, 5, 6	200	EPDM:	AS-RCV 1RVa 1RVb
	8	125	-20°F ~ +180°F (-29°C ~ +82°C)	1RVc 1RVd 1RVe 1RVf
SJ-200 Low Profile Butterfly Valve	2, 2½, 3, 4, 6	125	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ200 1JNa 1JNb 1JNc 1JNd

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-300F Resilient Seated Butterfly Valve	2½, 3, 4, 5, 6	200	EPDM: -20°F + +180°F (-29°C ~ +82°C)	AS-SJ300F AS-SJ300F-a 1JLa 1JLb 1JLc 1JLd 1JLe 1JLf 1JLf
SJ-500L	1½, 2, 2½, 3	250	EPDM:	
Ball Valve	4, 6	200	$-20^{\circ}\text{F} \sim +180^{\circ}\text{F}$ $(-29^{\circ}\text{C} \sim +82^{\circ}\text{C})$	SJ500-C-3
SJ-900 Swing Check Valve	2½, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F	AS-SJ900 1J9a 1RVb 1RVc
	8	150	(-29°C ~ +82°C)	1RVd 1RVe 1RVf
SJ-930 Horizontal Swing Check Valve	2, 21/2, 3, 4	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ930 1AJa 1AJb 1AJc AS-7771 H108a AS-XH70EP H1X8 G15a 7705TB 160a S819001
SJ-915 Dual Disc Check Valve	2½, 3, 4, 6, 8	300		AS-SJ915 AS-SJ915_b
	10, 12	150	EPDM: -20°F ~ +180°F	1JKa 1JKb
	14, 16, 18, 20, 24	100	(-29°C ~ +82°C)	1JKc 1JKd 1JKe