## UL Product iQ™



## HLCV7.EX6134 - Strainers, Pipeline Certified for Canada

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <a href="https://www.ul.com/about/locations">https://www.ul.com/about/locations</a>.

## Strainers, Pipeline Certified for Canada

## **Aalberts integrated piping systems APAC Inc**

EX6134

295 SEC 3 WANDAN RD WANDAN TOWNSHIP PINGTUNG HSIEN, 913 Taiwan

Strainer, Y type, sizes 2, 2-1/2, 3, 4, 5 and 6 in., for rated pressure of 300 psig (@) and sizes 8, 10 and 12 in., for rated pressure of 175 psig (\$) Model(s) 726

- (\$) Note: 5 mm screen opening size being 6.5 mm apart applicable with all the listed pipeline sizes
- (@) Note: 5mm screen opening size being 7 mm apart

 ${\it Trademark and/or\ Tradename:\ "SHURJOINT"},\ SHURJOINT",$ 

Last Updated on 2021-09-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"