

SS-59 Stainless Steel Groove x Thread NIPPLE




Shurjoint standard fitting pressure ratings conform to the ratings of Model 7707 couplings.

For pressure rating, listing, and approval information, refer to data sheet or visit SHURJOINT website www.shurjoint.com for details or contact your SHURJOINT representatives.

material specification

- **Fitting body:**
Type 304 Stainless steel



Gr. x Th.

Model SS-59 Nipple				
Nominal Pipe Size	Pipe O.D.	E-E	Weight	
in	in	in	lbs	
mm	mm	mm	kg	
1½	1.900	4	0.77	
40	48.3	102	0.35	
2	2.375	4	1.08	
50	60.3	102	0.49	
2½	2.875	4	1.70	
65	73.0	102	0.77	
3	3.500	4	2.09	
80	88.9	102	0.95	

General note

- Field Joint Test: For one time only, the system may be tested hydrostatically at 1½ times the maximum working pressure listed (AWWA C606 5.2.3).
- Warning: Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- The 10 Year Limited Warranty applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- Shurjoint reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.